



Product Data Sheet

STEPMASTER STAIRNOSINGS

STEPMASTER 700 SERIES

Stepmaster offers a comprehensive range of architecturally designed profiles to meet every demand, from heavy duty traffic in railway stations to the more general retail/office use, providing maximum pedestrian safety and WHS requirements. Stepmaster Stair Nosings are manufactured to meet and exceed the Australian standards and building codes.

SPECIFICATIONS

PRODUCT	Stepmaster 700 Series
CODE	SMN717
BASE MATERIAL	Alloy: 6060, Temper: T5
FINISH	Clear Anodised – 25Um
TREAD WIDTH	74mm
FRONT DEPTH	16mm
TREAD THICKNESS	4.8mm
INSERT TYPE	Anodised Alloy: 6060, Temper: T5
PRODUCT WARRANTY	2 Years (As per Walmay's standard warranty conditions)
INSERT SLIP RATING	P5 Classification (Highest available)
CODE COMPLIANCE	AS1428.1-2009 Check floor finish colour for luminance contrast requirements
FIXING METHOD	Screw fixed
APPLICATION	Surface mounted on hard floor finishes – Concrete, Timber etc.

*STANDARD COLOURS

Aluminium



CLEAR ANODISED



BLACK ANODISED



GOLD ANODISED

Insert



CLEAR ANODISED




BLACK ANODISED




GOLD ANODISED

*Other colours available on request



PROFILE




A 74mm

B 16mm

* Insert measures 54mm wide

TYPICAL INSTALLATION

Screw fixed



Concrete Substrate

HOW TO SPECIFY

Copy the prewritten specification below and update all sections in brackets to create your project specification.

Description

Stepmaster stairnosing profile series 700, Code: SMN717 in (Clear/Black/Sovereign Gold) anodised finish aluminium with insert colour (Clear/Black/Sovereign Gold). To be installed to the manufacturer's instructions in accordance to the AS/NZS 1428.1.4.2009

Manufacturer

Walmay Architectural Products Pty Ltd
 P: 1300 393 493
 E: sales@walmay.com.au
 W: www.walmay.com.au

Example – Typical Specification

Stepmaster stairnosing profile 700 series, SMN717 in clear anodised aluminium finish, with insert colour clear anodised. To be installed in accordance to the manufacturer's instructions in accordance to the AS/NZS 1428.1.4.2009