



Product Data Sheet

MONUMAT ENTRANCE MATTING


ALPHA GRIP 2 (02-AG2)

This profile utilises an aluminium tread rail with a flexible rubber joiner. The rubber joiner can be punched with specially placed holes to assist in the drainage of the mat well area. The system comes complete with a 31mm carborundum grit insert. An ideal profile for use in educational facilities, commercial buildings and retail outlets where water drainage is a priority.

SPECIFICATIONS

PRODUCT	Alpha Grip 2
CODE	Grip (02-AG2)
PROFILE LENGTH	Up to 6500mm modules
PROFILE WIDTH	50mm wide treadrail with 31mm wide inserts
PROFILE DEPTH	12mm
DESCRIPTION	Rollup hard wearing entrance mat with rubber backing
APPLICATION	Heavy duty - internal/external
SUPPORT CHASSIS	Anodised aluminium
TREAD SURFACE	Grip - Carborundum Grit
CONNECTION	Aluminium Interlocking hinge (ball and socket)
AVAILABLE COLOURS	Grip - 7

PROFILE



A	31mm
B	50mm
C	12mm

CHOOSE YOUR INSERT COLOUR

Grip

Grip is a combination of carborundum grit and epoxy creating a premium product that provides a safe, anti-slip finish. Ideal for locations where slip risk is high.

Other colours available on request



CHOOSE YOUR ALUMINIUM FINISH

Clear Anodised

A process for producing a translucent film of aluminum oxide which forms an integral part of the aluminum. This creates a very thin coating of immense hardness. Standard anodising is 15-20um (microns).



Black Anodised

Follows the same process as clear anodising but the aluminium is immersed into a tank full of dye which absorbs into the pores of the anodised coating until the depth of colour is obtained.



HOW TO SPECIFY

Copy the prewritten specification below and update all sections in brackets to create your project specification.

Description

Monumat Alpha-Grip 2 profile in (clear/black) anodised finish aluminium with (nominate insert colour) insert to be installed within (MF1235/RF1296) (clear/black) anodised aluminium perimeter frame.

Example - Typical Specification

Monumat Alpha-Grip 2 profile in clear anodised finish aluminium with charcoal insert to be installed within MF1235 clear anodised aluminium perimeter frame.