



Product Data Sheet


STEPMASTER STAIRNOSINGS

STEPMASTER 100 SERIES (SMN114)

SPECIFICATIONS

PRODUCT	Stepmaster 100 Series SMN114
BASE MATERIAL	Clear Anodised – 25Um
TREAD WIDTH	75mm
FRONT DEPTH	35mm
TREAD THICKNESS	4.8mm
INSERT TYPE	Solid Epoxy Based Carborundum – Heavy Duty, External Grade
INSERT WIDTH	Heavy duty - internal/external
INSERT COLOURS	Black, Safety Yellow, Grey, Red, Luminescent – other colours on request.
INSERT SLIP RATING	P5 Classification (Highest available)
CODE COMPLIANCE	AS1428.1-2009 Check floor finish colour for luminance contrast requirements
FEATURES	Pre-drilled and countersunk for secret screw fixing – Once installed, insert covers all fixings. Designed for use over plush pile carpets
OPTIONS	Available in black anodised aluminium

PROFILE



A 75mm

B 35mm

STANDARD COLOURS

Other colours available on request



BLACK




SAFETY YELLOW



GREY




RED



LUMINESCENT

TYPICAL INSTALLATION METHOD



STEPMASTER STAIRNOSING

“Defines the Lines”

Step Master offers a comprehensive range of architecturally designed profiles to meet every demand, from heavy duty traffic in railway stations to the more general retail/office use, providing maximum pedestrian safety and WHS requirements. Step Master Stair Nosing's are manufactured to meet and exceed the Australian standards and building codes.