




Product Data Sheet

STEPMASTER STAIRNOSINGS


STEPMASTER 400 SERIES (SMN418)

SPECIFICATIONS

PRODUCT	Stepmaster 400 Series SMN418
BASE MATERIAL	Alloy: 6060, Temper: T5
FINISH	Clear Anodised – 25Um
TREAD WIDTH	82mm
FRONT DEPTH	10mm
TREAD THICKNESS	12mm
INSERT TYPE	Carborundum tape – Heavy Duty, External Grade
INSERT WIDTH	54mm
INSERT COLOURS	Black, Safety Yellow, Grey, White – other colours on request.
INSERT SLIP RATING	P5 Classification (Highest Available)
CODE COMPLIANCE	AS1428.1-2009 Check floor finish colour for luminance contrast requirements.
FEATURES	Profile installed prior to carpet tiles. Holds carpet tiles on tread and riser. Pre-drilled and countersunk for secret screw fixing – Once installed, insert covers all fixings.
OPTIONS	Available in black anodised aluminium




PROFILE



A	82mm
B	10mm
C	22mm

STANDARD COLOURS

Other colours available on request



BLACK




SAFETY YELLOW



GREY

TYPICAL INSTALLATION METHOD



STEPMASTER STAIRNOSING

“Defines the Lines”

Step Master offers a comprehensive range of architecturally designed profiles to meet every demand, from heavy duty traffic in railway stations to the more general retail/office use, providing maximum pedestrian safety and WHS requirements. Step Master Stair Nosing's are manufactured to meet and exceed the Australian standards and building codes.